

General Information

Item	Q'ty	Thread dia.(mm)	Torque	Remarks
			N · m (kg-m, ft-lb)	
Steering adjustment nut	1	24	25 (2.5, 18)	NOTE 6 See page 12-15.
Fork pinch bolt (upper)	2	8	23 (2.3, 17)	
(lower)	2	10	40 (4.0, 29)	
Front axle bolt	1	14	60 (6.0, 43)	
Front axle pinch bolt	4	8	22 (2.2, 16)	
Front brake disc bolt	12	8	43 (4.3, 31)	NOTE 2
Rear Wheel/Rear Suspension:				
Drive chain adjuster lock nut	2	6	22 (2.2, 16)	
Rear axle nut	1	18	95 (9.5, 69)	
Shock absorber mounting nut	2	10	45 (4.5, 33)	
Shock link nut (frame side)	1	10	45 (4.5, 33)	
Shock link nut (shock arm side)	1	10	45 (4.5, 33)	NOTE 9
Shock arm bolt	1	10	45 (4.5, 33)	NOTE 9
Swingarm pivot nut	1	14	110 (11.0, 80)	
Drive chain adjuster lock nut	2	8	22 (2.2, 16)	NOTE 2
Rear brake disc bolt	4	8	43 (4.3, 31)	NOTE 6
Driven sprocket nut	4	12	90 (9.0, 65)	
Brake System :				
Rear master cylinder mounting bolt	2	6	12 (1.2, 9)	
Rear brake master cylinder reservoir bolt	1	6	9 (0.9, 7)	NOTE 2
Front brake caliper bracket bolt	4	8	27 (2.7, 20)	
Brake hose bolt	6	10	35 (3.5, 25)	
Front master cylinder holder bolt	2	6	12 (1.2, 9)	
Brake lever pivot nut	1	6	6 (0.6, 4)	
Breeder screw	3	8	6 (0.6, 4.3)	
Brake pipe three way joint bolt	1	6	10 (1.0, 7)	
Brake pad pin	5	8	18 (1.8, 13)	
Brake pad pin plug	5	8	3 (0.3, 2.2)	NOTE 6
Brake pipe flare nut	2	10	17 (1.7, 12)	NOTE 2
Caliper bracket pin bolt	3	5	13 (1.3, 9)	NOTE 2
Front brake caliper pin bolt	2	8	23 (2.3, 17)	
Rear brake caliper bracket bolt	1	10	23 (2.3, 17)	
Rear brake caliper pin bolt	1	10	28 (2.8, 20)	