

SPECIFICATIONS

SECTION/SUBJECT	GL1500 I '92	GL1500 I '93
ENGINE		
Configuration/Cylinders.....	6 Cylinders	
Strokes.....	4 strokes	
Cooling.....	Water cooled	
Camshaft.....	OHC	
Displacement.....	1520 cc	
Lubrication system.....	Wet sump	
Carburetor	12.4 in (36 mm)	
Main jet.....	# 148	
Slow jet.....	# 65	
TRANSMISSION		
Transmission type.....	Constant mesh	
Transmission speeds.....	5 Speeds	
Clutch.....	Wet, multi-plate	
Shift pattern.....	1-N-2-3-4-OD	
CHASSIS		
Fuel tank capacity (Std).....	6.3 U.S. gal (24.0 liters)	
Fuel tank capacity (Res).....	1.0 U.S. gal (3.8 liters)	
Air filter type.....	Paper	
Front brake.....	Double disc	
Rear brake.....	Single disc	
Front tire.....	130/70-18 63H	
Tire pressure.....	33 PSI	
Rear tire.....	160/80-16 75H	
Tire pressure.....	41 PSI	
SERVICE/TUNING		
Ignition type.....	Full transistor	
Spark plug gap.....	0.031-0.035 in (0.8-0.9 mm)	
LUBRICANTS		
Recommended fuel.....	86 Octane or higher	
Engine oil - Pro Honda		
GN4 10W40.....	08206-1040	
GN4 20W50.....	08206-2050	
Engine oil capacity:		
After draining.....	3.9 U.S. qt (3.7 liters)	
After reassembly.....	4.5 U.S. qt (4.3 liters)	
Coolant - Pro Honda.....	08204-0032	
Ratio.....	50/50	
Capacity.....	4.3 U.S. qt (4.1 liters)	
Drive shaft oil:		
Pro Honda Gear oil SAE 80W.....	08208-0080	
Capacity: After draining.....	4.7 U.S. oz (140 cc)	
After reassembly.....	5.7 U.S. oz (170 cc)	
Fork oil.....	ATF	
After reassembly.....	Left 10.9 U.S. oz (325 cc)	
	Right 10.8 U.S. oz (320 cc)	
Drake fluid - Pro Honda DOT 4.....	08203-0004	
Hydraulic clutch fluid -		
Pro Honda DOT 4 brake fluid.....	08203-0004	

REMARKS

REMARKS: SPECIFICATIONS LISTENING TO BE PROVIDED AT A LATER DATE.