

SPECIFICATIONS

DIMENSIONS

Overall length	1,600 mm (63.0 in)
Overall width	950 mm (37.4 in)
Overall height	940 mm (37.0 in)
Wheel base	1,015 mm (40.0 in)

WEIGHT

Dry weight	107 kg (236 lbs)
------------------	------------------

CAPACITIES

Engine oil	0.9 liter (0.95 US qt)
Fuel tank	6.0 liter (1.6 US gal)
Fuel reserve capacity	0.9 liter (0.26 US gal)
Passenger capacity	Operator only

ENGINE

Bore and stroke	52x49.5 mm (2.05x1.95 in)
Compression ratio	8.2 : 1
Displacement	105.1 cc (6.4 cu-in)
Contact breaker point gap	0.3–0.4 mm (0.012–0.016 in)
Spark plug gap	0.6–0.7 mm (0.024–0.028 in)
Valve clearance	0.07 mm (0.003 in)

CHASSIS AND SUSPENSION

Caster angle	68.5°
Trail length	61 mm (2.4 in)
Tire size, front and rear ...	22x11–8 ATV tire

POWER TRANSMISSION

Primary reduction	3.722
Final reduction	3.267
Gear ratio, 1st	2.538
2nd	1.611
3rd	1.190
4th	0.958
Posi-torque gear ratio	
Low range	1.867
High range	1.000