

TIRES

The ATC Big Red is equipped with low pressure tubeless tires to provide a comfortable ride. Although the tires are designed specifically for vigorous off-road use, they are not immune to punctures. Always select your riding area with care.

WARNING

** The ATC is not designed to be ridden on paved surfaces. Handling and control will be severely affected.*

Check tire pressure frequently with the air pressure gauge supplied with ATC.

For normal use, the tires should be inflated to a recommended pressure. A manually operated tire pump should be used rather than the high pressure systems found in service stations. This will minimize the possibility of tire damage from overinflation.

NOTE:

- * Tire pressure should be checked when the tires are “cold,” before you ride.
- * Check the tire pressure before you ride.

| TIRE SIZE | | 25X12.00-9 | |
|---------------------------|--------|---|---------------------|
| STANDARD TIRE BRAND | USA | FRONT | PRO/AM 501 Ohtsu |
| | | REAR | |
| | CANADA | FRONT | PRO/AM 501 Ohtsu |
| | | REAR | AT-503 Ohtsu |
| RECOMMENDED PRESSURE | | 2.2 psi (15 kPa, 0.15 kg/cm ²) | |
| MAX. PRESSURE | | 2.6 psi (18 kPa, 0.18 kg/cm ²) | |
| MIN. PRESSURE | | 1.8 psi (12 kPa, 0.12 kg/cm ²) | |

WARNING

- * *Maintain proper tire air pressure. Improperly inflated tires may adversely affect maneuverability and may cause loss of control.*
- * *When replacing tires use only the size, type and brand identified in the chart. The use of different sizes or types of tire can severely effect vehicle handling.*