

SPECIFICATIONS

| DIMENSIONS | |
|-----------------------|--------------------------------|
| Overall length | 1,887 mm (72.2 in) |
| Overall width | 1,137 mm (44.7 in) |
| Overall height | 1,038 mm (40.9 in) |
| Wheelbase | 1,237 mm (48.7 in) |
| WEIGHT | |
| Dry weight | 186 kg (413 lbs) |
| CAPACITIES | |
| Engine oil | 2.5 ℓ (2.6 US qt) |
| Fuel tank | 12 ℓ (3.1 US gal) |
| Fuel reserve capacity | 2.0 ℓ (0.52 US gal) |
| Passenger capacity | Operator only |
| ENGINE | |
| Bore and stroke | 74 x 57.3 mm (2.9 x 2.3 in) |
| Compression ratio | 9.0 : 1 |
| Displacement | 246 cc (15 cu-in) |
| Spark plug gap | 0.6–0.7 mm (0.023–0.028 in) |
| Valve clearance | 0.08 mm (0.003 in) |

| CHASSIS AND SUSPENSION | |
|---------------------------|--------------|
| Caster angle | 19.5° |
| Trail length | 0 mm (0 in) |
| Tire size, front and rear | 25 x 12.00–9 |
| POWER TRANSMISSION | |
| Primary reduction | 2.407 |
| Final reduction | 5.683 |
| Gear ratio, 1st | 2.388 |
| 2nd | 1.608 |
| 3rd | 1.178 |
| 4th | 0.906 |
| SL | 4.083 |
| Reverse gear ratio | 7.333 |