

SPECIFICATIONS

DIMENSIONS

Overall length
705 mm (27.8 in)
Overall width
1,025 mm (40.4 in)
Overall height
1,370 mm (53.9 in)
Wheelbase
130 mm (5.1 in)
Ground clearance

WEIGHT

Dry weight

170.0 kg (374.8 lbs)

CAPACITIES

Engine oil

3.1 & (3.3 US qt, 2.7 imp qt) After disassembly
2.9 & (3.1 US qt, 2.6 imp qt) After draining

Fuel tank

11.5 & (3.04 US gal, 2.53 imp gal)

Fuel reserve

3.5 & (0.92 US gal, 0.77 imp gal)

Cooling system capacity

2.0 & (0.53 US gal, 0.44 imp gal)

Passenger capacity load

Operator and one passenger

157 kg (347 lbs)

Maximum weight capacity

ENGINE

Bore and stroke

55.0 × 42.0mm (2.16 × 1.65in)
11.5:1

Compression ratio

399 cm³ (24.3 cu-in)

Spark plug

CR8EH-9 (NGK)
U24FER-9 (ND)

Standard

For extended high speed riding

CR9EH-9 (NGK)
U27FER-9 (ND)

Spark plug gap

0.8- 0.9 mm (0.03- 0.04 in)
1,300±100rpm

Idle speed

1,400±100rpm (Call. model)

Valve clearance(cold) Intake

0.08 mm (0.003 in)

Exhaust

0.08 mm (0.003 in)