

Maintenance Schedule

Perform the Pre-ride Inspection (page 9) at each scheduled maintenance period.

I: Inspect and Clean, Adjust, Lubricate or Replace if necessary. C: Clean. L: Lubricate. R: Replace.

FREQUENCY		NOTE	Each race or about 2.5 hours	Every 3 races or about 7.5 hours	Every 6 races or about 15.0 hours	Every 9 races or about 22.5 hours	Every 12 races or about 30.0 hours	Ref. Page
ITEMS								
THROTTLE OPERATION			I					47
HOT START SYSTEM			I					53
AIR FILTER		(NOTE 1)	C					43
CRANKCASE BREATHER			I					45
SPARK PLUG			I					54
RADIATOR COOLANT		(NOTE 2)	I					41
VALVE CLEARANCE / DECOMPRESSOR SYSTEM		(NOTE 4)			I			55/62
ENGINE OIL		(NOTE 3)			R			36
ENGINE OIL FILTER		(NOTE 3)			R			37
ENGINE IDLE SPEED			I					48
PISTON AND PISTON RINGS					R			68
PISTON PIN							R	68
TRANSMISSION OIL					R			39
COOLING SYSTEM			I					41
DRIVE CHAIN			I, L	R				85
DRIVE CHAIN SLIDER			I					85
DRIVE CHAIN ROLLER			I					86
DRIVE SPROCKET			I					87
DRIVEN SPROCKET			I					87
BRAKE FLUID		(NOTE 2)	I					79
BRAKE PADS WEAR			I					81
BRAKE SYSTEM			I					78
CLUTCH SYSTEM			I					49
CONTROL CABLES			I, L					93
EXHAUST PIPE/MUFFLER			I					88
SUSPENSION			I					73, 74
SWINGARM/SHOCK LINKAGE				L				25, 74
FORK OIL	FORK TUBE/SLIDER	(NOTE 3)		R				75
	DAMPER					R		102
NUTS, BOLTS, FASTENERS			I					94, 149-151
WHEELS/TYRES			I					82-84
STEERING HEAD BEARINGS						I		93

This maintenance schedule is based upon average riding condition. Machine subjected to severe use require more frequent servicing.

- NOTE: 1.Clean after every heat for dusty riding condition.
 2.Replace every 2 years. Replacement requires mechanical skill.
 3.Replace after the first break-in ride.
 4.Inspect after the first break-in ride.