

Specifications

■ Bulbs

Headlight	LED
Brakelight	LED
Taillight	LED
Front turn signal lights	LED
Rear turn signal lights	LED
License plate light	LED

■ Fuses

Main fuse	A	30A
	B	65A
Other fuses	30A, 20A, 10A	

■ Torque Specifications

Engine oil drain bolt	29 N·m (3.0 kgf·m, 21 lbf·ft)
Oil filter	26 N·m (2.7 kgf·m, 19 lbf·ft)
Final drive oil fill hole cap	12 N·m (1.2 kgf·m, 9 lbf·ft)
Final drive oil drain bolt	20 N·m (2.0 kgf·m, 15 lbf·ft)
Front wheel axle bolt	59 N·m (6.0 kgf·m, 44 lbf·ft)
Front wheel brake caliper mounting bolts	31 N·m (3.2 kgf·m, 23 lbf·ft)
Front wheel axle pinch bolts	27 N·m (2.8 kgf·m, 20 lbf·ft)
Rear wheel axle nut	98 N·m (10.0 kgf·m, 72 lbf·ft)
Rear wheel brake caliper stopper bolt	69 N·m (7.0 kgf·m, 51 lbf·ft)
Rear wheel axle pinch bolts	27 N·m (2.8 kgf·m, 20 lbf·ft)