

Specifications

■ Main Components

Type	RC69		
Overall length	2,255 mm (88.8 in)		
Overall width	CTX700A	Except KO type	855 mm (33.7 in)
		KO type	825 mm (32.5 in)
	CTX700D	840 mm (33.1 in)	
Overall height	1,165 mm (45.9 in)		
Wheelbase	1,530 mm (60.2 in)		
Minimum ground clearance	130 mm (5.1 in)		
Caster angle	Except KO type	27° 42'	
	KO type	27° 40'	
Trail	114 mm (4.5 in)		
Curb weight	CTX700A	Except KO type	226 kg (498 lb)
		KO type	225 kg (496 lb)
	CTX700D	234 kg (516 lb)	
Maximum weight capacity*1	Except KO type	190 kg (419 lb)	
	KO type	170 kg (375 lb)	
Maximum luggage weight (Except KO type)	15.5 kg (34 lb)		
Passenger capacity	Rider and 1 passenger		
Minimum turning radius	3.0 m (9.9 ft)		

*1 Including rider, passenger, all luggage, and accessories

Displacement	670 cm ³ (40.9 cu-in)	
Bore x stroke	73 x 80 mm (2.9 x 3.1 in)	
Compression ratio	10.7:1	
Fuel	Unleaded petrol Recommended: 91 RON or higher	
Tank capacity	12.4 litres (3.28 US gal, 2.73 Imp gal)	
Battery	YTZ12S 12V-11.0Ah (10 HR)/11.6Ah (20 HR)	
Gear ratios	CTX700A	
	1st	2.812
	2nd	1.894
	3rd	1.454
	4th	1.200
	5th	1.033
	6th	0.837
	CTX700D	
	1st	2.666
	2nd	1.904
	3rd	1.454
	4th	1.200
5th	1.033	
6th	0.837	
Reduction ratios (primary / final)	CTX700A	1.731 / 2.687
	CTX700D	1.921 / 2.437