

SPECIFICATIONS

DIMENSIONS

Overall length	2,630 mm (103.5 in)
Overall width	955 mm (37.6 in)
Overall height	1,525 mm (60.0 in)
Wheelbase	1,700 mm (66.9 in)
Ground clearance	140 mm (5.5 in)

WEIGHT

Dry weight	366 kg (807 lbs)
------------	------------------

CAPACITIES

Engine oil	3.5 ℓ (3.1 Imp qt, 3.7 US qt)
	After draining
Final drive gear oil	140 cm ³ (4.9 Imp oz, 4.7 US oz)
	After draining
Fuel tank	24.0 ℓ (5.3 Imp gal, 6.3 US gal)
Cooling system capacity	4.1 ℓ (3.6 Imp qt, 4.3 US qt)
Passenger capacity load	Operator and one passenger
Maximum weight capacity	185 kg (408 lb)

ENGINE

Bore and stroke	71 x 64 mm (2.8 x 2.5 in)
Compression ratio	9.8 : 1
Displacement	1,520 cc (92.7 cu.in)
Spark plug	
Standard	X22EPR-U9 (ND), DPR7EA-9 (NGK)
For cold climate (Below 5°C, 41°F)	X20EPR-U9 (ND), DPR6EA-9 (NGK)
For extended high speed riding	X24EPR-U9 (ND), DPR8EA-9 (NGK)
Spark plug gap	0.8—0.9 mm (0.031—0.036 in)
Idle speed	800 ± 80 rpm

CHASSIS AND SUSPENSION

Caster	30°
Trail	115 mm (4.5 in)
Tyre size, front	130/70-18 63H
Tyre size, rear	160/80-16 75H