

MOTORCYCLE SAFETY

LOADING AND ACCESSORIES

WARNING

- *To prevent an accident, use extreme care when adding and riding with accessories and cargo. Addition of accessories and cargo can reduce a motorcycle's stability, performance and safe operating speed. Never ride an accessory-equipped motorcycle at speeds above 130 km/h (80 mph). And remember that this 130 km/h (80 mph) limit may be reduced by installation of non-Honda accessories, improper loading, worn tyres and overall motorcycle condition, poor road or weather conditions. These general guidelines may help you decide whether or how to equip your motorcycle, and how to load it safely.*

Loading

The combined weight of the rider, passenger, cargo and additional accessories must not exceed the maximum weight capacity:

180 kg (397 lbs) ... **SE** (E, F, ED, FI, AR, SP)

175 kg (386 lbs) ... **SE** (SW)

185 kg (408 lbs) ... **SE** (SI)

182 kg (401 lbs) ... **ASP**

Cargo weight alone should not exceed:

27 kg (60 lbs)

1. Keep cargo and accessory weight low and close to the center of the motorcycle. Load weight equally on both sides to minimize imbalance. As weight is located further from the motorcycle's center of gravity, handling is proportionally affected.
2. Adjust tyre pressure (page 32), and rear suspension (pages 18–20) to suit load weight and riding conditions.
3. All cargo and accessories must be secure for stable handling. Recheck cargo security and accessory mounts frequently.