

- \* A manually operated tire pump should be used rather than the high pressure systems found in service stations. This will minimize the possibility of tire damage from overinflation.

	FRONT	REAR
TIRE SIZE	AT23 × 8-11 ★★	AT25 × 11-9 ★
TIRE BRAND	ATT911 GOOD YEAR	ATT912 GOOD YEAR
RECOMMENDED PRESSURE	20 kPa (0.20 kg/cm <sup>2</sup> , 2.9 psi)	20 kPa (0.20 kg/cm <sup>2</sup> , 2.9 psi)
MAXIMUM PRESSURE	23 kPa (0.23 kg/cm <sup>2</sup> , 3.3 psi)	23 kPa (0.23 kg/cm <sup>2</sup> , 3.3 psi)
MINIMUM PRESSURE	17 kPa (0.17 kg/cm <sup>2</sup> , 2.5 psi)	17 kPa (0.17 kg/cm <sup>2</sup> , 2.5 psi)

Fig. 4-32

Tire specifications

## ▲ WARNING

### POTENTIAL HAZARD

**Operating this ATV with improper tires, or with uneven tire pressure.**

### WHAT CAN HAPPEN

**Use of improper tires on this ATV, or operation of this ATV with improper or uneven tire pressure, may cause loss of control, increasing your risk of an accident.**

### HOW TO AVOID THE HAZARD

**Always use the size and type tires specified in this Owner's Manual for this vehicle.**

**Always maintain proper tire pressure as described in this Owner's Manual.**