## **Specifications**

Dimensions	
overall length	2,055 mm (80.9 in)
overall width	1,172 mm (46.1 in)
overall height	1,148 mm (45.2 in)TRX420TM
	1,146 mm (45.1 in)TRX420FM
wheelbase	1,256 mm (49.4 in)TRX420TM
	1,249 mm (49.2 in)TRX420FM
ground clearance	165 mm (6.5 in)

Fuel & Lubricants	
fuel	unleaded petrol, research octane
recommendation	number of 91 or higher
fuel tank capacity	13.3 l (3.51 US gal , 2.93 Imp gal)
	including reserve
fuel tank reserve	2.6 $\ell$ (0.69 US gal , 0.57 lmp gal)
engine oil capacity	after disassembly:
	3.1 l (3.3 US qt , 2.7 Imp qt)
	after draining:
	2.7 l (2.9 US qt , 2.4 lmp qt)
	after draining & oil filter change:
	2.8 l (3.0 US qt , 2.5 lmp qt)
engine oil	API Service Classification SE, SF or
recommendation	SG
	Honda 4-stroke oil or an equivalent
cooling system	High quality ethylene glycol
recommendation	antifreeze containing corrosion
	protection inhibitors specifically
	recommended for use in aluminum
	engines
cooling system	1.5 ½ (1.6 US qt , 1.3 lmp qt)
capacity	