

PROTECTIVE APPAREL

1. Most motorcycle accident fatalities are due to head injuries: ALWAYS wear a helmet. You should also wear a face shield or goggles; boots, gloves, and protective clothing.
2. The exhaust system becomes very hot during operation, and it remains hot after operation. Never touch any part of the hot exhaust system. Wear clothing that fully covers your legs.
3. Do not wear loose clothing which could catch on the control levers, kickstarter, footpegs, drive chain, or wheels.

MODIFICATIONS

WARNING

- * Modification of the motorcycle, or removal of original equipment may render the vehicle unsafe or illegal. Obey all federal, state, and local equipment regulations.*

LOADING AND ACCESSORIES

A motorcycle is sensitive to changes in weight distribution. Improper loading of cargo can impair the motorcycle's stability and performance. To prevent an accident, use extreme care when riding with cargo. These general guidelines may help you decide whether or how to equip your motorcycle.

Loading

The vehicle capacity load limit is 330lbs. The combined weight of the rider, passenger and cargo must not exceed this limit.

1. Keep cargo weight low and close to the center of the motorcycle. Load weight equally on both sides to minimize imbalance. As weight is located farther from the motorcycle's center of gravity, handling is proportionally affected.
2. All cargo must be secure for stable handling. Re-check cargo security frequently.