

SPECIFICATIONS

		'85:	AFTER '85:
DIMENSIONS	Overall length	1,895 mm (74.6 in)	1,905 mm (75.0 in)
	Overall width	1,120 mm (44.1 in)	1,130 mm (44.5 in)
	Overall height	1,090 mm (42.9 in)	1,085 mm (42.7 in)
	Wheelbase	1,295 mm (51.0 in)	1,305 mm (51.4 in)
	Seat height	760 mm (29.9 in)	780 mm (30.7 in)
	Foot peg height	360 mm (14.2 in)	340 mm (13.4 in)
	Ground clearance	120 mm (4.7 in)	110 mm (4.3 in)
	Dry weight	132 kg (291 lb)	131 kg (289 lb)
	Weight distribution	Front Rear	53.0 kg (117 lb) 79.0 kg (174 lb)
FRAME	Type	Semi double cradle	
	Front suspension and travel	Telescopic fork, 250 mm (9.84 in)	
	Rear suspension and travel	Swingarm, Pro-link, 250 mm (9.84 in)	
	Front tire size type	23X8-11	
	Front tire pressure	30 kPa (0.3 kg/cm ² , 4.3 psi)	
	Rear tire size type	20X10-9	
	Rear tire pressure	20 kPa (0.25 kg/cm ² , 3.6 psi)	
	Front brake	Single disc (2 pot)	
	Rear brake	Single disc (2 pot)	
	Fuel capacity	9.8 lit. (2.6 U.S. gal., 2.16 Imp. gal.)	
	Fuel reserve capacity	2.0 lit. (0.53 U.S. gal., 0.44 Imp. gal.)	
	Caster angle	21°	21°30'
	Trail length	37 mm (1.5 in)	38 mm (1.5 in)
Front fork oil	400 cc (13.5 U.S. oz, 0.35 Imp. qt)	464 cc (15.7 U.S. oz, 0.41 Imp. qt)	
ENGINE	Type	Water cooled, 2-stroke	
	Engine dry weight	26.0 kg (57.3 lb)	
	Cylinder arrangement	7° inclined from vertical, single	
	Bore x stroke	66 x 72 mm (2.60 x 2.83 in)	
	Displacement	246 cm ³ (15.01 cu.in)	
	Compression ratio	8.0	
	Transmission oil capacity	700 cc (24 U.S. oz, 0.62 Imp. qt.)	
	Lubrication system	Gasoline/oil mixture	
	Fuel required	Gasoline-oil ratio 20:1 (pre-mixed) (R O.N 92-100)	
	Air filtration	Oiled polyurethane form	