

Specifications

■ Main Components

Type	SC65	
Overall length	87.0 in (2,210 mm)	
Overall width	32.9 in (835 mm)	
Overall height	44.5 in (1,130 mm)	
Wheelbase	58.7 in (1,490 mm)	
Minimum ground clearance	4.92 in (125 mm)	
Caster angle	27° 00'	
Trail	4.5 in (114 mm)	
Curb weight	CB1100	540 lb (245 kg)
	CB1100A	549 lb (249 kg)
Maximum weight capacity*1	351 lb (159 kg)	
Passenger capacity	Rider and 1 passenger	
Minimum turning radius	8.86 ft (2.70 m)	

*1 Including rider, passenger, all luggage, and accessories

Displacement	69.5 cu-in (1,140 cm ³)	
Bore x stroke	2.89 x 2.65 in (73.5 x 67.2 mm)	
Compression ratio	9.5:1	
Fuel	Unleaded gasoline Recommended fuel octane number: Pump Octane Number (PON) 86 or higher.	
Tank capacity	3.86 US gal (14.6 liters)	
Battery	YTZ14S	
	12V-11.2Ah (10 HR)	
Gear ratios	1st	3.166
	2nd	2.062
	3rd	1.545
	4th	1.250
	5th	1.111
Reduction ratios (primary / final)	1.652 / 2.166	