

## Specifications

### ■ Service Data

Tire size	Front	110/80R18M/C 58V
	Rear	140/70R18M/C 67V
Tire type	Radial, tubeless	
Recommended Tires	Front	BRIDGESTONE BT-54F RADIAL G DUNLOP D205F
	Rear	BRIDGESTONE BT-54R RADIAL G DUNLOP D205
Tire air pressure	Front	36 psi (250 kPa, 2.50 kgf/cm <sup>2</sup> )
	Rear	42 psi (290 kPa, 2.90 kgf/cm <sup>2</sup> )
Minimum tread depth	Front	0.06 in (1.5 mm)
	Rear	0.08 in (2.0 mm)
Spark plugs	(standard)	LMAR8A-9S (NGK)
Spark plug gap	0.031 to 0.035 in (0.80 to 0.90 mm)	
Idle speed	1,100 ± 100 rpm	

Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	
	After draining	4.0 US qt (3.8 liters)
Engine oil capacity	After draining & engine oil filter change	4.1 US qt (3.9 liters)
	After disassembly	5.2 US qt (4.9 liters)
	Recommended brake (clutch) fluid	Honda DOT 4 Brake Fluid