

Specifications

■ Main Components

| | |
|---------------------------|-----------------------------------|
| Type | SC60 |
| Overall length | 83.5 in (2,120 mm) |
| Overall width | 31.7 in (805 mm) |
| Overall height | 43.1 in (1,095 mm) |
| Wheelbase | 56.9 in (1,445 mm) |
| Minimum ground clearance | 5.1 in (130 mm) |
| Caster angle | 25° 00' |
| Trail | 3.9 in (99 mm) |
| Curb weight | 485 lb (220 kg) |
| Maximum weight capacity*1 | 384 lb (174 kg) |
| Passenger capacity | Rider and 1 passenger |
| Minimum turning radius | 9.2 ft (2.8 m) |
| Displacement | 60.9 cu-in (998 cm ³) |
| Bore x stroke | 2.95 x 2.22 in (75.0 x 56.5 mm) |
| Compression ratio | 11.2:1 |

*1 Including rider, passenger, all luggage, and accessories

| | | |
|------------------------------------|------------------------------------------------------------------------------------------------|-------|
| Fuel | Unleaded gasoline Recommended fuel octane number: Pump Octane Number (PON) 86 or higher. | |
| Tank capacity | 4.5 US gal (17 liters) | |
| Battery | YTZ10S 12V-8.6Ah (10HR) | |
| Gear ratios | 1st | 2.538 |
| | 2nd | 1.941 |
| | 3rd | 1.578 |
| | 4th | 1.363 |
| | 5th | 1.217 |
| | 6th | 1.115 |
| Reduction ratios (primary / final) | 1.604 / 2.750 | |