

■ Service Data

| | | |
|----------------------------|---|---|
| Tire size | Front | 120/70ZR17M/C 58W |
| | Rear | 160/60ZR17M/C 69W |
| Tire type | Radial, tubeless | |
| Recommended Tires | Front | PIRELLI SCORPION TRAIL E |
| | Rear | PIRELLI SCORPION TRAIL |
| Tire air pressure | Front | 36 psi (250 kPa, 2.50 kgf/cm ²) |
| | Rear | 42 psi (290 kPa, 2.90 kgf/cm ²) |
| Minimum tread depth | Front | 0.06 in (1.5 mm) |
| | Rear | 0.08 in (2.0 mm) |
| Spark plugs | (standard) | CPR8EA-9 (NGK) |
| Spark plug gap | 0.031 to 0.035 in (0.80 to 0.90 mm) | |
| Idle speed (no adjustment) | 1,200 ± 100 rpm | |
| Recommended engine oil | API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil | |

| | | |
|-----------------------------------|---|------------------------|
| Engine oil capacity | After draining | 2.6 US qt (2.5 liters) |
| | After draining & engine oil filter change | 2.9 US qt (2.7 liters) |
| | After disassembly | 3.4 US qt (3.2 liters) |
| Recommended brake fluid | Honda DOT 4 Brake Fluid | |
| Cooling system capacity | 1.48 US qt (1.40 liters) | |
| Recommended coolant | Pro Honda HP Coolant | |
| Recommended drive chain lubricant | Pro Honda HP Chain Lube or equivalent lubricant | |
| Drive chain slack | 1 3/8 to 1 3/4 in (35 to 45 mm) | |
| Standard drive chain | DID 520V0 | |
| | No. of links | 112 |
| Standard sprocket sizes | Engine sprocket | 15T |
| | Rear wheel sprocket | 41T |