

## Specifications

Maximum weight on rear carrier	22 lb (10 kg)
Maximum weight in right side pocket	1.0 lb (0.5 kg)
<b>CRF1000A II/D II</b>	
Passenger capacity	Rider and 1 passenger
Minimum turning radius	8.5 ft (2.6 m)
Displacement	60.9 cu-in (999 cm <sup>3</sup> )
Bore x stroke	3.62 x 2.96 in (92.0 x 75.1 mm)
Compression ratio	10.0 : 1
Fuel	Unleaded gasoline Recommended: 86 PON or higher
Tank capacity	<b>CRF1000A/D</b> 4.97 US gal (18.8 L) <b>CRF1000A II/D II</b> 6.39 US gal (24.2 L)
Battery	HY110 12 V-6 Ah (20 HR)

Gear ratio	<b>CRF1000A/A II</b>	
	1st	2.866
	2nd	1.888
	3rd	1.480
	4th	1.230
	5th	1.100
	6th	0.968
	<b>CRF1000D/D II</b>	
	1st	2.562
	2nd	1.761
	3rd	1.375
	4th	1.133
5th	0.972	
6th	0.882	
Reduction ratio (primary / final)	<b>CRF1000A/A II</b> 1.733 / 2.625 <b>CRF1000D/D II</b> 1.883 / 2.625	