

GL1800/B

■ Main Components

|                           |                               |                     |
|---------------------------|-------------------------------|---------------------|
| Overall length            | <b>GL1800</b>                 | 101.4 in (2,575 mm) |
|                           | <b>GL1800B</b>                | 97.4 in (2,475 mm)  |
| Overall width             | 36.4 in (925 mm)              |                     |
| Overall height            | <b>GL1800</b>                 | 56.3 in (1,430 mm)  |
|                           | <b>GL1800B</b>                | 52.8 in (1,340 mm)  |
| Wheelbase                 | 66.7 in (1,695 mm)            |                     |
| Minimum ground clearance  | 5.1 in (130 mm)               |                     |
| Caster angle              | 30.5°                         |                     |
| Trail                     | 4.3 in (109 mm)               |                     |
| Curb weight               | <b>GL1800 USA model</b>       | 833 lb (378 kg)     |
|                           | <b>GL1800 Canada model</b>    | 836 lb (379 kg)     |
|                           | <b>GL1800B USA model</b>      | 787 lb (357 kg)     |
|                           | <b>GL1800B Canada model</b>   | 805 lb (365 kg)     |
| Maximum weight capacity*1 | <b>GL1800</b>                 | 423 lb (192 kg)     |
|                           | <b>GL1800B</b>                | 421 lb (191kg)      |
| Maximum luggage weight    | Travel trunk (Except GL1800B) | 20.0 lb (9.0 kg)    |
|                           | Each saddlebag                | 20.0 lb (9.0 kg)    |
|                           | Fairing pocket                | 4.5 lb (2.0 kg)     |
|                           | Shelter case                  | 6.6 lb (3.0 kg)     |
| Passenger capacity        | Rider and 1 passenger         |                     |
| Minimum turning radius    | 11.2 ft (3.4 m)               |                     |

\*1 Including rider, all luggage, and accessories

|   |  |       |
|---|--|-------|
| Displacement                                  | 111.8 cu-in (1,833 cm <sup>3</sup> )               |       |
| Bore x stroke                                 | 2.87 x 2.87 in (73.0 x 73.0 mm)                    |       |
| Compression ratio                             | 10.5:1   |       |
| Fuel  | Unleaded gasoline<br>Recommended: 86 PON or higher |       |
| Tank capacity                                 | 5.5 US gal (21 liters)                             |       |
| Battery                                       | GYZ20L   |       |
|   | 12 V-20 Ah (10 HR)                                 |       |
| Gear ratio                                    | 1st  | 2.200 |
|   | 2nd  | 1.416 |
|   | 3rd  | 1.035 |
|   | 4th  | 0.820 |
|   | 5th  | 0.666 |
|   | 6th  | 0.521 |
| Reduction ratio (primary / secondary / final) | 1.795 / 0.972 / 2.615                              |       |

■ Service Data

|                        |   |   |
|------------------------|---|---|
| Tire size              | Front   | 130/70R18M/C 63H                            |
|                        | Rear  | 200/55R16M/C 77H                            |
| Tire type              | Radial, tubeless  |   |
| Recommended Tire       | Front   | BRIDGESTONE G853 RADIAL G DUNLOP D423F      |
|                        | Rear  | BRIDGESTONE G852 RADIAL G DUNLOP D423       |
| Tire air pressure      | Front   | 36 psi (250 kPa, 2.50 kgf/cm <sup>2</sup> ) |
|                        | Rear  | 41 psi (280 kPa, 2.80 kgf/cm <sup>2</sup> ) |
| Minimum tread depth    | Front   | 0.06 in (1.5 mm)                            |
|                        | Rear  | 0.08 in (2.0 mm)                            |
| Spark plug             | (standard)  | CR6H5B-9 (NGK)                              |
| Spark plug gap         | 0.031 to 0.035 in (0.80 to 0.90 mm)   |   |
| Idle speed             | (non-adjustable)  | 730 ± 100 rpm                               |
| Recommended engine oil | API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil |   |
|                        | After draining  | 3.7 US qt (3.5 liters)                      |
| Engine oil capacity    | After draining & engine oil filter change   | 3.9 US qt (3.7 liters)                      |
|                        | After disassembly   | 4.6 US qt (4.4 liters)                      |