

# Specifications

---

| <b>Torque Specification</b>         |                                    |
|-------------------------------------|------------------------------------|
| seat-back mount bolts               | 9 lbf·ft (12 N·m , 1.2 kgf·m)      |
| engine oil drain bolt               | 18 lbf·ft (25 N·m , 2.5 kgf·m)     |
| engine oil filter bolt              | 13 lbf·ft (18 N·m , 1.8 kgf·m)     |
| maintenance lid mount bolts         | 9 lbf·ft (12 N·m , 1.2 kgf·m)      |
| right seat mount pipe mount bolt A  | 16 lbf·ft (22 N·m , 2.2 kgf·m)     |
| right seat mount pipe mount bolts B | 20 lbf·ft (27 N·m , 2.8 kgf·m)     |
| front differential oil drain bolt   | 9 lbf·ft (12 N·m , 1.2 kgf·m)      |
| front differential oil fill cap     | 9 lbf·ft (12 N·m , 1.2 kgf·m)      |
| rear differential oil drain bolt    | 9 lbf·ft (12 N·m , 1.2 kgf·m)      |
| rear differential oil fill cap      | 9 lbf·ft (12 N·m , 1.2 kgf·m)      |
| spark arrester mount bolts          | 9 lbf·ft (12 N·m , 1.2 kgf·m)      |
| wheel nuts                          | 79.7 lbf·ft (108 N·m , 11.0 kgf·m) |