

Specifications

■ Service Data

Tire size	Front	120/70ZR18M/C (59W)
	Rear	200/50ZR17M/C (75W)
Tire type	Radial, tubeless	
Recommended Tires	Front	DUNLOP D423F K
	Rear	DUNLOP D423 K
Tire air pressure	Front	33 psi (225 kPa, 2.25 kgf/cm ²)
	Rear	36 psi (250 kPa, 2.50 kgf/cm ²)
Minimum tread depth	Front	0.06 in (1.5 mm)
	Rear	0.08 in (2.0 mm)
Spark plugs	(standard)	IFR6G-11K (NGK)
Spark plug gap	(non-adjustable)	0.039 to 0.043 in (1.00 to 1.10 mm)
Idle speed	(non-adjustable)	1,200 ± 100 rpm

Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	
	After draining	3.4 US qt (3.2 liters)
Engine oil capacity	After draining & engine oil filter change	3.6 US qt (3.4 liters)
	After draining, engine & clutch oil filter change	3.6 US qt (3.4 liters)
	After disassembly	4.3 US qt (4.1 liters)
Recommended brake fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	1.79 US qt (1.69 liters)	