

## Specifications

Gear ratio	<b>NC700X/750XA</b>	
	1st	2.812
	2nd	1.894
	3rd	1.454
	4th	1.200
	5th	1.033
	6th	0.837
	<b>NC700XD/750XD</b>	
	1st	2.666
	2nd	1.904
	3rd	1.454
	4th	1.200
	5th	1.033
6th	<b>NC700XD</b>	0.837
	<b>NC750XD</b>	0.864
Reduction ratio (primary / final)	<b>NC700X</b>	1.731 / 2.687
	<b>NC700XD</b>	1.921 / 2.437
	<b>NC750XA</b>	1.731 / 2.529
	<b>NC750XD</b>	1.921 / 2.294

## ■ Service Data

Tire size	Front	120/70ZR17M/C(58W)
	Rear	160/60ZR17M/C(69W)
Tire type	Radial, tubeless	
Recommended Tire	Front	DUNLOP D609F
		BRIDGESTONE BW-501 RADIAL G
	Rear	DUNLOP D609
		BRIDGESTONE BW-502 RADIAL G
Tire air pressure	Front	36 psi (250 kPa, 2.50 kgf/cm <sup>2</sup> )
	Rear	42 psi (290 kPa, 2.90 kgf/cm <sup>2</sup> )
Minimum tread depth	Front	0.06 in (1.5 mm)
	Rear	0.08 in (2.0 mm)
Spark plug	(standard)	IFR6G-11K (NGK)
Spark plug gap	(non-adjustable)	0.039 - 0.043 in (1.00 - 1.10 mm)
Idle speed	1,200 ± 100 rpm	
Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	