

Engine oil capacity	NC700X/750XA	
	After draining	3.3 US qt (3.1 L)
	After draining & engine oil filter change	3.6 US qt (3.4 L)
	After disassembly	3.9 US qt (3.7 L)
	NC700XD/750XD	
	After draining	3.4 US qt (3.2 L)
	After draining & engine oil filter change	3.6 US qt (3.4 L)
Recommended brake fluid	After draining, engine & clutch oil filter change	3.6 US qt (3.4 L)
	After disassembly	4.3 US qt (4.1 L)
	Honda DOT 4 Brake Fluid	
Cooling system capacity	1.79 US qt (1.69 L)	
Recommended coolant	Pro Honda HP Coolant	
Recommended drive chain lubricant	Pro Honda HP Chain Lube or equivalent	
Drive chain slack	1 3/16 - 1 9/16 in (30 - 40 mm)	

Standard drive chain	DID 520V0 or RK 520KHO	
	NC700X/750XA	
Standard sprocket size	No. of links	114
	NC700XD/750XD	
Standard sprocket size	No. of links	112
	NC700X/XD	
	Drive sprocket	16T
	NC750XA/XD	
	Drive sprocket	17T
	NC700X/750XA	
Standard sprocket size	Driven sprocket	43T
	NC700XD/750XD	
Standard sprocket size	Driven sprocket	39T

■ Bulbs

Headlight	12 V-60/55 W
Brake light/Taillight	LED
Front turn signal light	12 V-21/5 W x 2
Rear turn signal light	12 V-21 W x 2
License plate light	12 V-5 W