

■ Service Data

Tire size	Front	80/100-10 46J
	Rear	80/100-10 46J
Tire type	Bias-ply, tubeless	
Recommended Tires	Front	CHENG SHIN C6161
	Rear	CHENG SHIN C6161
Tire air pressure	Front	18 psi (125 kPa, 1.25 kgf/cm ²)
	Rear	29 psi (200 kPa, 2.00 kgf/cm ²)
Spark plug	CPR8EA-9 (NGK)	
Spark plug gap	0.031 to 0.035 in (0.80 to 0.90 mm)	
Idle speed	2,000 ± 100 rpm	
Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MB, Pro Honda HP4M 4-stroke oil or an equivalent motorcycle oil	

Engine oil capacity	After draining	0.68 US qt (0.64 liters)
	After draining & engine oil strainer screen cleaning	0.69 US qt (0.65 liters)
	After disassembly	0.74 US qt (0.7 liters)
Cooling system capacity	0.33 US qt (0.31 liters)	
Recommended coolant	Pro Honda HP Coolant	

■ Bulbs

Headlight	12V-35/35W
Brake/Taillight	12V-21/5W
Front turn signal lights	12V-10W x 2
Rear turn signal lights	12V-10W x 2

■ Fuses

Main fuse	25A
Other fuse	10A

■ Torque Specifications

Engine oil drain bolt	18 lbf-ft (24 N-m, 2.4 kgf-m)
Engine oil plug	15 lbf-ft (20 N-m, 2.0 kgf-m)