

# Quick Reference

Tires	<b>Front:</b> SXS1000M3/M3P/M5P 27X9.00-12 NHS BLACKSTONE OTR HP-009 SXS1000M3L/M5D/M5L 27X9.00R14 NHS MAXXIS BIGHORN 2.0 <b>Rear:</b> SXS1000M3/M3P/M5P 27X11.00-12 NHS BLACKSTONE OTR HP-009 SXS1000M3L/M5D/M5L 27X11.00R14 NHS MAXXIS BIGHORN 2.0
Tire Pressure (cold)	<b>Front:</b> SXS1000M3/M3P/M5P/M5D 13 psi (90 kPa) SXS1000M3L/M5L 14 psi (100 kPa) <b>Rear:</b> 14 psi (100 kPa)
Spark Plugs	standard: <b>SILMAR7A9S (NGK)</b>
Coolant	Ethylene glycol antifreeze (silicate-free) for aluminum engines in 50/50 solution with Pro Honda HP Coolant or an equivalent distilled water
Fuses	main: <b>50 A</b> circuit: SXS1000M3/M3P/M5P/M5D 30 A, 20 A, 15 A × 4, 10 A × 3 SXS1000M3L/M5L 30 A × 2, 20 A, 15 A × 4, 10 A × 3 EPS (except for SXS1000M3): <b>40 A</b> BTCS (SXS1000M3L/M5L only): <b>40 A</b>