

Specifications

Fuses	
main	50 A
circuit	SXS1000M3/M3P/M5P/M5D 30 A, 20 A, 15 A × 4, 10 A × 3 SXS1000M3L/M5L 30 A × 2, 20 A, 15 A × 4, 10 A × 3
EPS (except for SXS1000M3)	40 A
BTCS (SXS1000M3L/M5L only)	40 A

Torque Specification	
engine oil filter cover bolts	9 lbf·ft (12 N·m, 1.2 kgf·m)
DCT oil filter cover bolts	9 lbf·ft (12 N·m, 1.2 kgf·m)
engine oil drain bolts (oil pan and oil tank)	22 lbf·ft (30 N·m, 3.1 kgf·m)
sub-transmission oil drain bolt	22 lbf·ft (29 N·m, 3.0 kgf·m)
front final gear oil fill cap	9 lbf·ft (12 N·m, 1.2 kgf·m)
front final gear oil drain plug	9 lbf·ft (12 N·m, 1.2 kgf·m)
rear final gear oil fill cap	9 lbf·ft (12 N·m, 1.2 kgf·m)
rear final gear oil drain plug	9 lbf·ft (12 N·m, 1.2 kgf·m)
spark arrester mount bolts	9 lbf·ft (12 N·m, 1.2 kgf·m)
wheel nuts	80 lbf·ft (108 N·m, 11 kgf·m)