## **Specifications**

Torque Specification	
passenger handhold	13 lbf·ft (17 N·m, 1.7 kgf·m)
adjusting nut	
passenger handhold	20 lbf·ft (26.5 N·m, 2.7 kgf·m)
lock nut	
engine oil filter	9 lbf·ft (12 N·m, 1.2 kgf·m)
cover bolts	
DCT oil filter	9 lbf·ft (12 N·m, 1.2 kgf·m)
cover bolts	
engine oil drain	21 lbf·ft (29 N·m, 3.0 kgf·m)
bolts (oil pan and	
oil tank)	
sub-transmission	21 lbf·ft (29 N·m, 3.0 kgf·m)
oil drain bolt	
front final gear oil	9 lbf·ft (12 N·m, 1.2 kgf·m)
fill cap	0    ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( (
front final gear	9 lbf·ft (12 N·m, 1.2 kgf·m)
oil drain plug	0    ( ( ( ( 4 2 N
rear final gear oil	9 lbf·ft (12 N·m, 1.2 kgf·m)
check bolt	0 ll- f ft /42 N 4 2 l ( )
rear final gear oil	9 lbf·ft (12 N·m, 1.2 kgf·m)
fill cap	0 lbf ft (12 N m 1 2 kgf m)
rear final gear oil	9 lbf·ft (12 N·m, 1.2 kgf·m)
drain plug	3.7 lbf·ft (5 N·m, 0.5 kgf·m)
air cleaner mounting screws A and B	5.7 IDI-IL (5 N·III, U.5 KGI·III)
	9 lbf·ft (11.8 N·m, 1.2 kgf·m)
spark arrester mount bolts	3 IDI'IL (11.0 IN'III, 1.2 KYI'III)
wheel nuts	90 lbf.ft (109 N.m. 11 kgf.m)
wheel huts	80 lbf·ft (108 N·m, 11 kgf·m)