

■ Service Data

| | | |
|---------------------|---------------------|---|
| Tire size | Front | 90/90-21M/C 54H |
| | Rear | 200/50R18M/C 76H |
| Tire type | Front | Bias-ply, tubeless |
| | Rear | Radial, tubeless |
| Recommended Tires | Front | DUNLOP D422F METZELER ME880 |
| | Rear | DUNLOP D423 METZELER ME880 |
| Tire air pressure | Front | 33 psi (225 kPa, 2.25 kgf/cm ²) |
| | Rear | 41 psi (280 kPa, 2.80 kgf/cm ²) |
| Minimum tread depth | Front | 0.06 in (1.5 mm) |
| | Rear | 0.08 in (2.0 mm) |
| Spark plugs | (standard) | DCPR6E (NGK) or XU20EPR-U (DENSO) |
| | (high speed riding) | DCPR7E (NGK) or XU22EPR-U (DENSO) |
| Spark plug gap | (non-adjustable) | 0.031 to 0.035 in (0.80 to 0.90 mm) |
| Idle speed | | 930 ± 100 rpm |

| | | |
|-----------------------------|---|----------------------------------|
| Recommended engine oil | API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil | |
| | After draining | 3.7 US qt (3.5 liters) |
| Engine oil capacity | After draining & filter change | 3.9 US qt (3.7 liters) |
| | After disassembly | 4.5 US qt (4.3 liters) |
| Recommended final drive oil | Hypoid gear oil SAE 80 | |
| Final drive oil capacity | After draining | 4.4 US oz (130 cm ³) |
| | After disassembly | 5.7 US oz (170 cm ³) |
| Recommended brake fluid | Honda DOT 4 Brake Fluid | |
| Cooling system capacity | 2.68 US qt (2.54 liters) | |
| Recommended coolant | Pro Honda HP Coolant | |