

■ Bulbs

| | |
|-------------------------|-----------------|
| Headlight | 12 V-60/55 W |
| Brake light/Taillight | 12 V-21/5 W |
| Front turn signal light | 12 V-21/5 W x 2 |
| Rear turn signal light | 12 V-21 W x 2 |
| License plate light | 12 V-5 W |

■ Fuses

| | |
|------------|------------|
| Main fuse | 30 A |
| FI fuse | 15 A |
| Other fuse | 20 A, 10 A |

■ Torque Specifications

| | |
|-------------------------------|---------------------------------|
| Battery cover screw | 0.7 lbf-ft (1 N-m, 0.1 kgf-m) |
| Seat mounting bolt B | 19 lbf-ft (26 N-m, 2.7 kgf-m) |
| Engine oil drain bolt | 21 lbf-ft (29 N-m, 3.0 kgf-m) |
| Oil filter | 19 lbf-ft (26 N-m, 2.7 kgf-m) |
| Final drive oil fill hole cap | 9 lbf-ft (12 N-m, 1.2 kgf-m) |
| Final drive oil drain bolt | 9 lbf-ft (12 N-m, 1.2 kgf-m) |
| Front wheel axle bolt | 44 lbf-ft (59 N-m, 6.0 kgf-m) |
| Front wheel axle pinch bolt | 16 lbf-ft (22 N-m, 2.2 kgf-m) |
| Rear brake stopper arm nut | 16 lbf-ft (22 N-m, 2.2 kgf-m) |
| Rear wheel axle nut | 65 lbf-ft (88 N-m, 9.0 kgf-m) |
| Rear wheel axle holding bolt | 20 lbf-ft (27 N-m, 2.8 kgf-m) |
| Exhaust pipe joint nut | 18 lbf-ft (25 N-m, 2.5 kgf-m) |
| Muffler bracket nut | 32 lbf-ft (44 N-m, 4.5 kgf-m) |
| Footpeg bolt A, B and nut | 29 lbf-ft (39 N-m, 4.0 kgf-m) |
| Headlight bolt | 3.0 lbf-ft (4.1 N-m, 0.4 kgf-m) |