Specifications

■ Main Components

Overall length	75.8 in (1,925 mm	n)
Overall width	29.3 in (745 mm)	
Overall height	43.5 in (1,105 mm)	
Wheelbase	51.8 in (1,315 mm)	
Minimum ground clearance	5.3 in (135 mm)	
Caster angle	27° 00′	
Trail	3.3 in (85 mm)	
Curb weight	289 lb (131 kg)	
Maximum weight capacity *1	366 lb (166 kg)	
Maximum luggage weight	Center compartment	22 lb (10 kg)
	Front box	2.2 lb (1.0 kg)
Passenger capacity	Rider and 1 passenger	
Minimum turning radius	6.2 ft (1.90 m)	
Displacement *2	9.1 cu-in (149 cm ³)	

- *1: Including rider, passenger, all luggage, and accessories.
 *2: Displacement less than 9.2 cu-in (150 cm³) may have highway operating restrictions depending on state laws.

Bore x stroke	2.26 x 2.28 in (57.3 x 57.9 mm)
Compression ratio	10.6:1
Fuel	Unleaded gasoline Recommended fuel octane number:Pump Octane Number (PON) 86 orhigher
Tank capacity	2.11 US gal (8.0 L)
Battery	GTZ8V 12 V-7.0 Ah (10 HR)
Primary reduction	V-Matic (2.52:1 to 0.81:1)
Final reduction	9.854