

# MAINTENANCE SCHEDULE

Perform the PRE-RIDE INSPECTION in the Owner's Manual at each scheduled maintenance period.

I: Inspect and Clean, Adjust, Lubricate, or Replace if necessary.

R: Replace, L: Lubricate

The following items require some mechanical knowledge. Certain items (particularly those marked \* and \*\*) may require more technical information and tools. Consult your authorized Honda dealer.

ITEM	FREQUENCY	WHICHEVER COMES FIRST ↓ NOTE	ODOMETER READING (NOTE 1)								Refer to page
			x 1000 km	1	6	12	18	24	30	36	
			x 1000 mi	0.6	4	8	12	16	20	24	
EMISSION RELATED ITEMS	* FUEL LINE				I		I		I	NOTE 5	
	* THROTTLE OPERATION				I		I		I	NOTE 5	
	* CARBURETOR CHOKE				I		I		I	NOTE 5	
	AIR CLEANER	NOTE 2				R			R	3-5	
	SPARK PLUG			R	R	R	R	R	R	3-5/NOTE 5	
	* VALVE CLEARANCE		I				I			3-5	
	ENGINE OIL		R		R		R		R	NOTE 5	
	ENGINE OIL FILTER		R		R		R		R	NOTE 5	
	* CARBURETOR SYNCHRONIZATION				I		I		I	3-8/NOTE 5	
	* CARBURETOR IDLE SPEED		I	I	I	I	I	I	I	NOTE 5	
	RADIATOR COOLANT	NOTE 3			I		I		R	NOTE 5	
	* COOLING SYSTEM				I		I		I	NOTE 5	
	* SECONDARY AIR SUPPLY SYSTEM	NOTE 4				I		I		I	NOTE 5
	* EVAPORATIVE EMISSION CONTROL SYSTEM	NOTE 4					I		I		NOTE 5
NON-EMISSION RELATED ITEMS	DRIVE CHAIN		I, L EVERY 600 mi (1,000 km)								NOTE 5
	BRAKE FLUID	NOTE 3			I	I	R	I	I	R	NOTE 5
	BRAKE PAD WEAR				I	I	I	I	I	I	NOTE 5
	BRAKE SYSTEM		I		I		I		I		NOTE 5
	* BRAKE LIGHT SWITCH				I		I		I		NOTE 5
	* HEADLIGHT AIM				I		I		I		NOTE 5
	CLUTCH SYSTEM		I	I	I	I	I	I	I	I	NOTE 5
	SIDE STAND				I		I		I		3-8
	* SUSPENSION				I		I		I		NOTE 5
	* NUTS, BOLTS, FASTENERS		I		I		I		I		NOTE 5
	** WHEELS/TIRES				I		I		I		NOTE 5
** STEERING HEAD BEARINGS		I		I		I		I		NOTE 5	

\* Should be serviced by an authorized Honda dealer, unless the owner has proper tools and service data and is mechanically qualified.

\*\* In the interest of safety, we recommend these items be serviced only by an authorized Honda dealer.

NOTES: 1. At higher odometer readings, repeat at the frequency interval established here.

2. Service more frequently when riding in unusually wet or dusty areas.

3. Replace every 2 years, or at indicated odometer interval, whichever comes first. Replacement requires mechanical skill.

4. Californial type only.

5. Refer to the Common Service Manual.