

NOTE

- Shift the transmission into neutral before removing or installing the gearshift linkage.

Requisite Service

- Drive sprocket cover removal/installation (page 8-9)

Procedure		Qty	Remarks
	Removal Order		Installation is in the reverse order of removal.
(1)	Neutral switch mounting screw	1	
(2)	Neutral switch	1	<ul style="list-style-type: none"> • Disconnect the neutral switch connector. • Installation (page 8-12)
(3)	Neutral switch joint	1	
(4)	Gearshift linkage cover bolt	5	
(5)	Gearshift linkage cover	1	<ul style="list-style-type: none"> • Remove/install as an assembly. • Installation (page 8-12)
(6)	Gearshift spindle assembly	—	
(7)	— washer	1	
(8)	— snap ring	1	
(9)	— return spring	1	
(10)	Gasket	1	
(11)	Dowel pin	2	
(12)	Guide plate mounting bolt	1	
(13)	Guide plate/drum shifter assembly	—	Assembly: as illustrated
(14)	— guide plate	1	
(15)	— ratchet pawl	2	Pawl orientation as shown.
(16)	— plunger	2	
(17)	— spring	2	
(18)	— drum shifter	1	
(19)	Collar	1	
(20)	Dowel pin	2	
(21)	Stopper arm bolt	1	
(22)	Washer	1	
(23)	Stopper arm	1	
(24)	Spring	1	
(25)	Collar	1	
(26)	Washer	1	