

LIGHTS/METERS/SWITCHES

SPECIFICATIONS

ITEM		SPECIFICATIONS	
Bulbs	Headlight	Hi	12V - 60 W
		Lo	12V - 55 W
	Brake/tail light		12V - 21/5 W X 2
	Turn signal light	Front	12V - 23/8 W X 2
		Rear	12V - 21 W
	License light		12V - 5 W
	Instrument light		12V - 1.7 W X 3
	Turn signal indicator		12V - 1.7 W X 2
	High beam indicator		LED
	Neutral indicator		LED
	Oil pressure indicator		LED
	PGM-FI warning indicator		LED
	Fuel reserve indicator		LED
Fuse	Main fuse	30 A	
	PGM-FI fuse	20 A	
	Sub fuse	20 A X 1, 10A X 4	
Tachometer peak voltage		10.5 V minimum	
ECT sensor resistation	80 °C	2.1 - 2.6 k Ω	
	120 °C	0.62 - 0.76 k Ω	

TORQUE VALUES

Coolant temperature/ECT sensor	23 N·m (2.3 kgf·m, 17 lbf·ft)
Side stand switch bolt	10 N·m (1.0 kgf·m, 7 lbf·ft)
Ignition switch mounting bolt	25 N·m (2.5 kgf·m, 18 lbf·ft)
Fan motor switch	18 N·m (1.8 kgf·m, 13 lbf·ft)
Oil pressure switch	12 N·m (1.2 kgf·m, 9 lbf·ft)
Oil pressure switch wire terminal bolt/washer	2 N·m (0.2 kgf·m, 1.4 lbf·ft)
Neutral switch	12 N·m (1.2 kgf·m, 9 lbf·ft)

ALOC bolt; replace with a new one

Apply sealant to the threads
Apply sealant to the threads