

GENERAL INFORMATION

TRANSMISSION/GEARSHIFT LINKAGE:

ITEM	Q'TY	THREAD DIA. (mm)	TORQUE N·m (kgf·m, lbf·ft)	REMARKS
Gearshift pedal pivot bolt	1	8	22 (2.2, 16)	
Gearshift pedal link pinch bolt	1	6	9.8 (1.0, 7)	
Link arm lock nut	2	6	9.8 (1.0, 7)	

FRONT WHEEL/SUSPENSION/STEERING:

ITEM	Q'TY	THREAD DIA. (mm)	TORQUE N·m (kgf·m, lbf·ft)	REMARKS
Handlebar weight mounting screw	2	6	9.8 (1.0, 7)	NOTE 6
Handlebar pinch bolt	2	8	26 (2.7, 20)	
Front axle bolt	1	18	78 (8.0, 58)	
Front axle holder pinch bolt	4	8	22 (2.2, 16)	
Front brake disc bolt	12	6	20 (2.0, 14)	NOTE 6
Fork socket bolt	2	10	34 (3.5, 25)	
Fork bolt	2	46	34 (3.5, 25)	
Fork damper lock nut	2	14	25 (2.6, 19)	
Fork compression adjuster plug bolt	2	14	18 (1.8, 13)	
Fork top bridge pinch bolt	2	8	23 (2.3, 17)	
Fork bottom bridge pinch bolt	4	8	23 (2.3, 17)	
Steering damper second arm nut	1	6	12 (1.2, 9)	NOTE 5
Steering damper second arm bolt	1	6	8.8 (0.9, 6.5)	
Steering damper mounting bolt	3	6	8.8 (0.9, 6.5)	
Steering stem adjusting nut	1	26	20 (2.0, 14)	
Steering stem adjusting lock nut	1	26	-	See page 14-42
Steering stem nut	1	24	103 (10.5, 76)	

REAR WHEEL/SUSPENSION:

ITEM	Q'TY	THREAD DIA. (mm)	TORQUE N·m (kgf·m, lbf·ft)	REMARKS
Rear axle nut	1	22	113 (11.5, 83)	NOTE 5
Rear brake disc bolt	4	8	42 (4.3, 31)	NOTE 6
Final driven sprocket nut	6	10	64 (6.5, 47)	NOTE 5
Rear shock absorber upper mounting nut	1	10	44 (4.5, 33)	NOTE 5
Rear shock absorber lower mounting nut	1	10	44 (4.5, 33)	NOTE 5
Shock link-to-frame pivot nut	1	10	44 (4.5, 33)	NOTE 5
Shock arm-to-shock link nut	1	10	44 (4.5, 33)	NOTE 5
Shock arm-to-swingarm nut	1	10	44 (4.5, 33)	NOTE 5
Drive chain case flange bolt	3	6	12 (1.2, 9)	
Swingarm pivot adjusting bolt	1	36	15 (1.5, 11)	
Swingarm pivot adjusting bolt lock nut	1	36	64 (6.5, 47)	
Swingarm pivot nut	1	22	113 (11.5, 83)	
Drive chain slider bolt	3	6	8.8 (0.9, 6.5)	NOTE 2