

FRAME

LOCATION	MATERIAL	REMARKS
Side stand pivot Rider footpeg sliding area Passenger peg sliding area Rear brake pedal pivot sliding area Throttle grip pipe sliding surface Passenger seat catch hook sliding area Gearshift pedal pivot sliding area Front wheel dust seal lips Rear wheel dust seal lips Final driven flange O-ring Rear shock absorber pivot dust seal lips	Multi-purpose grease	
Steering head bearing adjusting nut threads Upper and lower steering head bearing Steering head dust seal lips	Urea based multi-purpose grease with extreme pressure (example: EXCELIGHT EP2 manufactured by KYODO YUSHI, Japan), Shell stamina EP2 or equivalent	0.1 - 0.3 g 3 - 5 g (each)
Swingarm pivot bearings Swingarm pivot dust seal lips Shock arm and shock link needle bearings Shock arm and shock link dust seal lips Gearshift pedal link tie-rod ball joints	Multi-purpose grease (Shell Alvania EP2 or equivalent)	
Throttle cable A, B cable inside	Cable lubricant	
Exhaust valve cable A, B cable inside	Molybdenum oil	
Handlebar grip rubber inside	Honda bond A, Pro Honda Handgrip Cement (U.S.A. only) or equivalent	
Front brake lever pivot/adjuster/push rod sliding area Front brake push rod and piston contacting area Rear brake caliper boot inside Rear brake master piston-to-push rod contact area Brake caliper dust seals Clutch lever sliding area and piston contact area Clutch pivot bushing and piston contact area	Silicone grease	
Brake master piston and cups Brake caliper piston and piston seals	DOT 4 brake fluid	
Fork cap O-ring Fork dust seal and oil seal lips	Pro Honda Suspension Fluid SS-55 or equivalent	
Rear brake reservoir hose joint screw threads Front master cylinder oil cup stay mounting bolt threads Front brake caliper assembly bolt threads Rear brake caliper pin bolt threads Clutch oil cup tightening screw threads	Locking agent	