

		mm	kg-m
Handle bar bolts	2	8	2.4-3.0
Main switch bolts	2	8	2.4-3.0
Seat bolts	1	8	2.0-2.4
Fule cock	1	22	2.0-2.5
Clutch lever bracket bolt	2	6	0.7-1.1
Rear fork pivot bolt	1	14	6.0-7.0
Rear fork pivot lock nut	1	26	6.0-7.0
Rear fork pivot adjust bolt	1	26	1.0-2.0
Steering stem nut	1	24	9.0-12.0
Steering adjustment nut	1	26	2.3-2.7
Top bridge bolt	2	7	0.9-1.3
Bottom bridge bolt	2	10	4.5-5.5
Front brake barcket caliper bolt	4	8	2.4-3.0
Front brake master cylinder bolt	2	6	1.0-1.4
Brake hose bolt	5	10	2.5-3.5
Front axle hose stay bolt	3	6	1.0-1.4
Front brake pipe	2	10	1.6-1.8
Bleeder valve bolt	3	7	0.4-0.7
Cushion conrod bolt (frame)	1	10	6.0-7.0
(cushion arm)	1	10	6.0-7.0
Cushion arm bolt	1	10	6.0-7.0
Rear cushion upper bolt	1	12	6.0-7.0
Rear cushion lower bolt	1	10	6.0-7.0
Front brake disc bolt	6	6	1.4-1.6
Front fork socket bolt	2	8	1.5-2.5
Front fork bolt	2	35	1.5-3.0
Driven sprocket nut	6	8	2.8-3.4
Rear cushion lwr joint lock nut	1	12	6.0-7.5
Rear cushion lower joint	1	12	3.8-6.0
Rear brake disc bolt	3	8	3.7-4.3
Front brake hangler pin	4	10	1.5-2.0
Rear brake hanger pin retainer bolt	1	6	0.8-1.3
Rear caliper pin bolt	1	10	2.4-3.0
Rear caliper bolt	1	8	2.0-2.5

STANDARD TORQUES

6 mmSH: : 8 mm

Size	Torque (kg-m)	Size	Torque (kg-m)
5mm bolt, nut	0.45-0.6	5 mm screw	0.35-0.5
6mm bolt, nut	0.8-1.2	6 mm screw 6 mm SH	0.7-1.1
8mm bolt, nut	1.8-2.5	6 mm flange bolt, nut	1.0-1.4
10mm bolt, nut	3.0-4.0	8 mm flange bolt, nut	2.4-3.0
12mm bolt, nut	5.0-6.0	10mm flange bolt, nut	3.5-4.5