

		6	12		
WHEEL	Tire Pressures	●	● ●	Frt	Rear
				1 rider	2.25      2.25
				2 riders	2.25      2.50
				Tire type	.10/70R17 54H   150.60R18 67H
	Tire wear and damage	●	● ●		
	Tire tread depth	●	● ●	Min - Frt 0.8mm	Rear 0.8mm
	Foreign articles struck in tires	●	● ●		
	Wheel nut, wheel bolt loosening			Tighten axle nut, axle holder front axle holder torque	1.8-2.5 Kg.m
				Fro axle bolt torque	5.5-6.5 Kg.m
				Rr axle nut torque	8.5-10.5 Kg.m
Rim, side rim, wheel disc damage	○	●	Wheel rim runout, warpage		
			Front	2.0mm axial 2.0mm radial	
			Rear	2.0mm axial 2.0mm radial	
Front wheel bearings		●			
Rear wheel bearing		●			
Rush Spring Arm	Damage		●	Tighten cushion, spring	
	Arm damage		●		
Shock Abs	Fluid leakage, damage		●		
	Busness		●		
Clutch	Lever play		● ●	Play - lever	10-20mm
	Use	○	● ●		
Trans	Fluid leakage, oil capacity		● ●	Oil capacity - between upper and lower marks	
	Gear movement		●		
P11	Transmission oil replacement			Every two years	