

NSR250R(J)

: mm

| | | | |
|--|--|------------------------|------|
| | | | |
| | | 0.30—0.45 | 0.50 |
| | | 0.30—0.45 | 0.50 |
| | | 10±2kg/cm ² | — |

: mm

| | | | |
|--|--|---------------|-------|
| | | | |
| | | 36.0 | 35.0 |
| | | 20.020—20.041 | 20.07 |
| | | 22.959—22.980 | 22.92 |
| | | 23.000—23.021 | 23.05 |

: mm

| | | | |
|--|--|---------------|-------|
| | | | |
| | | — | 0.2 |
| | | 0.02—0.07 | 0.12 |
| | | 0.10—0.15 | 0.2 |
| | | 24.987—24.993 | 24.95 |

: mm

| | | | |
|--|--|-----------|------|
| | | | |
| | | 0.54—0.76 | 0.85 |

: mm

| | | | |
|--|--|-------------|--------|
| | | | |
| | | 15.4—20.0kg | 12.3kg |
| | | 160.3 | — |
| | | 172.3 | 168.9 |

: mm

| | | | |
|--|---|---------------|--------|
| | | | |
| | A | 25.400—25.450 | 25.46 |
| | B | 30.230—30.280 | 30.29 |
| | | 38.180—38.230 | 38.24 |
| | A | 25.318—25.368 | 25.31 |
| | B | 30.148—30.198 | 30.14 |
| | | 38.115—38.148 | 38.105 |
| | | 14.000—14.043 | 14.055 |
| | | 13.957—13.984 | 13.945 |

| | | | |
|--|--|---------|---------|
| | | | |
| | | 429cc | — |
| | | 128mm | — |
| | | 267.2mm | 261.9mm |