

**General Information**

Unit: mm (in)

<b>Wheels/Tires</b>	<b>Item</b>	<b>Standard</b>	<b>Service limit</b>
	Cold tire pressure (Front)	125 kPa (1.25 kg/cm <sup>2</sup> , 18 psi)	_____
	(Rear)	200 kPa (2.00 kg/cm <sup>2</sup> , 29 psi)	_____
	Front and rear axle runout	_____	0.2 (0.008)
	Front and rear wheel rim runout (Radial)	_____	2.0 (0.08)
	(Axial)	_____	2.0 (0.08)
	Drive chain slack	_____	_____
	Drive chain size/link (DID)	_____	_____
	(RK)	_____	_____

<b>Front Suspension</b>			
	Fork spring free length	133.5 (5.26)	129.5 (5.10)
	Fork spring free length A	_____	_____
	B	_____	_____
	Fork spring direction	Tightly wound coil facing up	_____
	Fork tube runout	_____	_____
	Recommended fork oil	_____	_____
	Fork oil level	_____	_____
	Fork oil level (Right)	_____	_____
	(Left)	_____	_____
	Fork oil capacity	_____	_____
	Fork oil capacity (Right)	_____	_____
	(Left)	_____	_____
	Fork air pressure	_____	_____
	Steering bearing preload	_____	_____

<b>Rear Suspension</b>			
	Shock absorber spring free length	_____	_____
	Shock absorber spring free length A	_____	_____
	B	_____	_____
	Shock absorber spring direction	_____	_____
	Damper drilling point	_____	_____

<b>Brakes</b>			
	Front brake fluid	_____	_____
	brake lever free play	10-20 (0.4-0.8)	_____
	brake disc thickness	_____	_____
	brake disc runout	_____	_____
	master cylinder I.D.	_____	_____
	master piston O.D.	_____	_____
	caliper cylinder I.D.	_____	_____
	caliper piston O.D.	_____	_____
	brake drum I.D.	95.0 (3.74)	95.5 (3.76)
	brake lining thickness	3.0 (0.12)	1.0 (0.04)
	Rear brake fluid	_____	_____
	brake lever free play	10-20 (0.4-0.8)	_____
	brake pedal free play	_____	_____
	brake disc thickness	_____	_____
	brake disc runout	_____	_____
	master cylinder I.D.	_____	_____
	master piston O.D.	_____	_____
	caliper cylinder I.D.	_____	_____
	caliper piston O.D.	_____	_____
	brake drum I.D.	95.0 (3.74)	95.5 (3.76)
	brake lining thickness	3.0 (0.12)	1.0 (0.04)